

# Polyester Varnish

NAME OF ENAMEL	THERMAL CLASS	SOLID CONTENT %	VISCOSITY (POISE)	APPLICABL WIRE DIA. mm	SUITABLE OVEN TYPE	COATING METHOD	FEATURES
YPE107	B	40~43	10~65	0.5~2.0	V	D	For Vertical Oven.
YPE107T	B	40~43	10~65	0.5~2.0	V	D	Wild working conditions.
YPE108	B	30~35	0.5~2.0	0.06~0.5	H	F	For Horizontal Oven.
YPE108T	B	30~35	0.5~2.0	0.06~0.5	H	F	Wild working conditions.
YPE162	B~F	30	1.0~1.6	0.06~0.5	H	D	Improved Thermal.
YPE165	F	33~40	2~25	0.2~0.6	H	D	Improved Thermal.
YBH103	B~F	37~40	8~28	0.3~2.0	H · V	D	Improved Heat Shock.
YBH105	B~F	40	25~40	0.5~2.0	V	D	Improved Heat Shock.
YBH106	B~F	24~40	0.4~15	0.5~2.0	H · V	F · D	Improved Heat Shock.

※H : HORIZONTAL OVEN   V : VERTICAL OVEN   F : FELT   D : DIES